

PHYS-E6570 Solar Energy Engineering (5 cr); 1st half-exam, 15 February 2016

You may use a calculator in the exam.

1. You have two alternatives to choose from:

The Sun is a huge energy source driven by fusion reactions.

- Estimate Sun's radiative power based on its effective surface temperature and diameter.
- How large fraction of Sun's radiation hits the Earth?
- Estimate the solar constant (= incident radiation intensity per m² above the atmosphere).

The effective surface temperature of the Sun is 5762 K and its diameter is 1.39×10^9 m. The mean distance between the Sun and the Earth is 1.5×10^{11} m, and the radius of the Earth 6370 km. Stefan Boltzmann constant is $\sigma = 5.670373 \times 10^{-8} \text{ W m}^{-2} \text{ K}^{-4}$

/OR/ Explain all main components and operating principle of a solar heating system.

2. The reflectance ρ of a surface is one of the key optical parameters in solar energy engineering. It determines both the absorptance α and emittance ε of a surface.

- Illustrate in a diagram the reflectance values (y-axis, 0-100%) as a function of the wavelength (x-axis, nm) of an ideal selective absorber for a solar thermal collector. What is the total absorptance and emittance values of an optimal selective absorber over the whole spectrum of interest?
- Give 2 examples how to realize a selective absorber surface. Short answers only.
- What is the equilibrium temperature of an ideal selective absorber in full sunshine? Stefan Boltzmann constant is $\sigma = 5.670373 \times 10^{-8} \text{ W m}^{-2} \text{ K}^{-4}$

3. The amount of solar radiation on a surface can be increased through sun-tracking by following the movement of the sun and trying to minimize the incidence angle θ_i .

Let's assume that we have a so-called 1-axis tracker with the following geometry: north-south axis (NS-axis) and east-west tracking (EW-tracking). The surface is vertical. Determine the incidence angle of beam radiation on the surface using the solar azimuth γ_s and solar zenith angles θ_z .

4. A solar heating system consists of solar collectors that have the following parameter values: $F_R \tau \alpha = 0.7$ and $F_R U_L = 2 \text{ W/m}^2 \text{ K}$ in the Hottel-Whillier-Bliss (HWB) equation.

- What kind of collector could this be? (1p)
- Draw the efficiency curve of the solar collector using $(T_{fi} - T_a)/G$ as x-axis (2p)
- How high temperature could the collector reach on a sunny warm summer day, if the circulation pump is turned off? (3p)

5. Give a short and precise answer to each of the following questions, 2-3 lines for each.

- Air mass
- Maximum concentration ratio
- Pyranometer
- Ratio of diffuse radiation on a vertical surface to a horizontal surface
- Amount of solar radiation on an optimally inclined surface: Helsinki, Vienna, Rome or a sun-belt country in kWh/m² per year. Choose one country only.
- Thermosiphon